

GUARD I FIRE HOSE

General:

“Guard” Type 1 layflat fire hose is made of polyester staple and filaments weaved single jacket with internal extruded EPDM rubber lining. It is a flexible, seawater, heat, abrasion, aging and ozone resistance. It is washable, lightweight, durable and economical fire fighting hose conforming to BS6391 Type I standard with minimum friction loss due to a very smooth internal rubber lining.



GUARD I

Applications

- Municipal Fire Brigades
- Marine Vessels
- Industrial Fire Brigades
- Refineries
- Irrigation

Approvals:

- UL Listed for 1-1/2” and 2-1/2”

Technical Data:

Diameter	mm	38	45	50	63	70	76	102	127	152
	Inches	1 1/2	1 3/4	2	2 1/2	2 3/4	3	4	5	6
Burst Pressure (min)	kgf/cm ²	50	50	50	50	50	42	38	38	38
Proof Pressure	kgf/cm ²	25	25	25	25	25	21	19	19	19
Kink Test Pressure	kgf/cm ²	25	25	25	25	25	21	19	19	19
Working Pressure	kgf/cm ²	17	17	17	17	17	15	15	15	15
30m Length coil diameter	cm	45	55	55	55	55	60	60	60	60
Mass per Meter (Max.)	gm	275	320	350	425	480	650	800	1000	1200
Abrasion Resistance (Min.)	Cycles	100	100	100	100	100	100	100	100	100
(at 7kg /cm² Pressure)										
Heat Resistance	Sec (Min.)	8	8	8	8	8	8	8	8	8



ASSOCIATED ENTERPRISES (S) PTE. LTD.

BLOCK 28, #01-171-177 SIN MING DRIVE SINGAPORE 575702

TEL : (65) 6455 0555 FAX : (65) 6455 0505

EMAIL: enquiry@aespl.com.sg WEBSITE: www.aespl.com.sg

Co. Reg. No. 197900283H GST No. M2-0033562-7



Lic. No.: WMKA21084
WMK05528

0620

Lic. No.: KM551487
KM551486